

# AVTREKKER KUKKO 21-5-E 34-48MM INNVENDIG



Produktnummer: 203373

The perfect tool for pulling out ball bearings, ball bearing races, sleeves and bushes, puller length 110mm pulling diameter 34mm - 48mm. For extracting bearings, bearing outer rings and bushings that lay flat on one another.

## Description

The segmented design with extra fine grasp edges ensures safe extraction.  
Mechanical pressure screw.

## Advantage

Kukko internal extractors can be combined with counter supports and slide hammers.  
Almost all components available as replacement parts, time-saving order process thanks to numbering system.

## Goes with

22-2 Counterstay

## How it works

Place the internal extractor into the bearing's hole.  
Using a ring spanner, tighten the nuts to open the jaws of the internal extractor. Make sure that the jaws sit securely below the bearing's inner race.  
For removal, the spindle on the counter support series 22 or on the slide hammer series 22-0 is screwed onto the key spindle on the internal extractor.

## Counter support:

2. The counter support's arms must not block the part due to be removed. Make sure that the arms are parallel.  
3. Hold on to the T-grip and at the same time use the jaw wrench to tighten the nuts above the cross-beam until the component has been loosened from its position.

## Slide hammer:

2. The part is extracted by using the slide hammer to exert powerful force until the component has been loosened from its position.

**Puller length:** 110mm

**Min pulling dia:** 34mm

**Max pulling dia:** 48mm

**Suitable for Kukko counterstay part no:** 22-2

**Suitable for Kukko slide hammer part no:** 22-0-1

- Mechanical pressure screw
- Milled thread treated with special coating
- The segmented design with extra fine grasp edges ensures safe extraction
- Kukko internal extractors can be combined with counter supports and slide hammers
- For extracting bearings, bearing outer rings and bushings that lay flat on one another

Made in Germany

## Spesifikasjoner



<b>Vekt</b>	0.215 kg
<b>Bredde/tykkelse</b>	0.0 mm
<b>Høyde</b>	0.0 mm
<b>Volum</b>	5.0 liter
<b>Dimensjon</b>	0.0
<b>Nøkkelvidde</b>	0.0 mm
<b>kW</b>	0.0
<b>Innvendig diameter</b>	0.0 mm
<b>Utvendig diameter</b>	0.0 mm
<b>Type</b>	ANNET
<b>Type 4</b>	0.0
<b>Delelengde</b>	0.0 mm
<b>Type 3</b>	0.0
<b>Bredde ytre ring</b>	0.0 mm
<b>Bredde indre ring</b>	0.0 mm
<b>Type 2</b>	0.0
<b>Type 5</b>	0.0
<b>Bordiameter</b>	0.0 mm
<b>Diameter</b>	0.0 mm
<b>Neseradius</b>	0.0 mm
<b>Antall tenner/rader/deling/spor</b>	0
<b>Bruksområde</b>	INNVEDIG
<b>Lengde</b>	0.0 mm

Les mer om produktet her:

<https://www.ail.no/product?number=203373>