

BETEX FLEXIBLE INDUCTOR 22KW, 20M', Ø12MM, MAX.180



Produktnummer: 210437

Flexible inductors are a multifunctional solution for various shapes or sizes. They can be used in or around a workpiece or both.



Min. winding diameter flexible inductors 3.5kW

| Length m | Max. temp. | Diameter cable | Min. winding diameter |
|----------|------------|----------------|-----------------------|
| 5/7.5/10 | 180°C | Ø 12 mm | ca. 90 mm |

Min. winding diameter flexible inductors 10kW

| Length m | Max. temp. | Diameter cable | Min. winding diameter |
|----------------|------------|----------------|-----------------------|
| 15/20/25/30 | 180°C | Ø 12 mm | ca. 75 mm |
| 15/20/25/30/35 | 180°C | Ø 15 mm | ca. 100 mm |
| 15/20/25/30/35 | 300°C | Ø 20 mm | ca. 120 mm |

Min. winding diameter flexible inductors 22kW

| Length m | Max. temp. | Diameter cable | Min. winding diameter |
|-------------|------------|----------------|-----------------------|
| 15/20/25/30 | 180°C | Ø 12 mm | ca. 75 mm |
| 15/20/25/30 | 180°C | Ø 15 mm | ca. 100 mm |

15/20/25/30

300°C

Ø 20 mm

ca. 120 mm

Min. winding diameter flexible inductors 44kW

| Length m | Max. temp. | Diameter cable | Min. winding diameter |
|-------------|------------|----------------|-----------------------|
| 15/20/25/30 | 180°C | Ø 19 mm | ca. 140 mm |
| 15/20/25/30 | 300°C | Ø 28 mm | ca. 220 mm |

Spesifikasjoner

| | |
|---------------------------------|------------|
| Vekt | 10.0 kg |
| Bredde/tykkelse | 0.0 mm |
| Høyde | 0.0 mm |
| Volum | 10.0 liter |
| Dimensjon | 0.0 |
| Nøkkelvidde | 0.0 mm |
| kW | 22.0 |
| Innvendig diameter | 0.0 mm |
| Utvendig diameter | 0.0 mm |
| Type 4 | 0.0 |
| Delelengde | 0.0 mm |
| Type 3 | 0.0 |
| Bredde ytre ring | 0.0 mm |
| Bredde indre ring | 0.0 mm |
| Type 2 | 0.0 |
| Type 5 | 0.0 |
| Bordiameter | 0.0 mm |
| Diameter | 0.0 mm |
| Neseradius | 0.0 mm |
| Antall tenner/rader/deling/spor | 0 |
| Lengde | 0.0 mm |



Les mer om produktet her:

<https://www.ail.no/product?number=210437>