

# BETEX FLEXIBLE INDUCTOR 22KW, 15M', Ø20MM, MAX.300



Produktnummer: 210438

Flexible inductors are a multifunctional solution for various shapes or sizes. They can be used in or around a workpiece or both.

## Min. winding diameter flexible inductors 3.5kW

Length m	Max. temp.	Diameter cable
5/7.5/10	180°C	Ø 12 mm



## Min. winding diameter flexible inductors 10kW

Length m	Max. temp.	Diameter cable	Min. winding diameter
15/20/25/30	180°C	Ø 12 mm	ca. 75 mm
15/20/25/30/35	180°C	Ø 15 mm	ca. 100 mm
15/20/25/30/35	300°C	Ø 20 mm	ca. 120 mm

## Min. winding diameter flexible inductors 22kW

Length m	Max. temp.	Diameter cable	Min. winding diameter
15/20/25/30	180°C	Ø 12 mm	ca. 75 mm
15/20/25/30	180°C	Ø 15 mm	ca. 100 mm

15/20/25/30

300°C

Ø 20 mm

ca. 120 mm

### Min. winding diameter flexible inductors 44kW

Length m	Max. temp.	Diameter cable	Min. winding diameter
15/20/25/30	180°C	Ø 19 mm	ca. 140 mm
15/20/25/30	300°C	Ø 28 mm	ca. 220 mm

### Spesifikasjoner

Vekt	10.0 kg
Bredde/tykkelse	0.0 mm
Høyde	0.0 mm
Volum	10.0 liter
Dimensjon	0.0
Nøkkelvidde	0.0 mm
kW	22.0
Innvendig diameter	0.0 mm
Utvendig diameter	0.0 mm
Type 4	0.0
Delelengde	0.0 mm
Type 3	0.0
Bredde ytre ring	0.0 mm
Bredde indre ring	0.0 mm
Type 2	0.0
Type 5	0.0
Bordiameter	0.0 mm
Diameter	0.0 mm
Neseradius	0.0 mm
Antall tenner/rader/deling/spor	0
Lengde	0.0 mm



Les mer om produktet her:

<https://www.ail.no/product?number=210438>